

The new Rope Grab has been designed to allow a user complete ease when ascending and descending a vertical rope, whilst still providing optimum safety.

- Allow user to connect and disconnect at any point along the line.
- Anti-Panic function ensures unit operates even in a panic situation.
- Double Action locking mechanism for ultimate user safety.
- For use with 16mm thick rope.
- Provides maximum freedom of movement when ascending and descending and whilst working off the line.
- Stainless Steel and Thermoplastic construction for protection and durability.
- Suitable for numerous applications where attachment to a flexible vertical lifeline is required.



Easy and simple to install.

Simply remove the detent pin, open the hinge and place the rope grab on the 16mm lifeline. Close the hinged gate and re-insert the detent pin. The rope grab is now fixed to the lifeline. Then simply connect your shock absorbing lanyard to both your rear D ring and the rope grab.

Easy and simple to use.

The rope grab travels freely up and down the rope with the user, without the need to manually reposition the rope grab.

The Rope Grab utilises a double locking inertia and cam mechanism which offers greater safety and eliminates 'panic-grab' situations.

The Rope Grab can be easily attached.

and removed anywhere along the lifeline, but utilises a double locking mechanism to ensure no accidental disengagement from the line. It offers users complete safety and peace of mind when working at height.

Versatile & Economical.

This lightweight system is reusable and transportable from one job site to another.

The revolutionary design enables it to be used on worn or new rope without any of those nuisance lock-ups. Complete with compatible connection point for your lanyard.

Rope Grab Model :

5000337 : Detent Rope Grab

Rope Grab Twisted Rope :

KC209/15: 16mm dia. 15m

KC209/20: 16mm dia. 20m

KC209/30: 16mm dia. 30m



Specifications :

Material: Stainless Steel mechanism, Thermoplastic case

Weight: 0.7kg

Capacity: 1 user (141kg)

Standards: BS EN 353-2 CE approved

Capital Safety

USA : 800.328.6146 • Canada : 800.387.7484 • Asie : + 65 6558 7758 • Australie : 1800 245 002 • Nouvelle-Zélande : 0800 212 505
Europe, Moyen-Orient, Afrique : +33 (0) 497 10 00 10 • Europe du Nord : +44 (0) 1928 57 1324

www.capitalsafety.com • information@capitalsafety.com

Réf. : A01ROPEGRABTDEN Ind. 0